

VX6 Rugged Vehicle-Mount Computer



VEHICLE-MOUNT COMPUTERS

Voice ready with ToughTalk™ technology for your voice-directed logistics applications.

High performance 802.11a/b/g radio for mobile connectivity to your enterprise network.



Available with heated touch screen - eliminates condensation, fog & ice build-up.

Supports LXE's RFTerm™ multi-session terminal emulator.

Ten dedicated function keys allow one-touch application functionality.



Low profile improves driver's field of view while driving.

"High-Vis" half-screen affords better visibility in low-light conditions.

Screen blanking safety feature.

Larger, backlit keys allow easy gloved-hand data entry.

LXE is RUGGED MOBILE COMPUTERS.

Flexible features for improved performance

The VX6 comprises an XScale® processor and Windows® CE .NET operating system offering CE .NET applications on both your handheld and vehicle-mounted computers while greatly reducing operator training time & support costs.

The VX6 ships voice ready with ToughTalk™ technology, a specialized combination of LXE's trademark rugged system design, advanced audio circuitry and noise-canceling techniques - for industrial-grade, voice logistics applications.

Future proofed for a greater ROI

The CE .NET architecture provides greater ROI by enabling you to easily adopt future emerging technologies and applications. The VX6 supports LXE's RFTerm® multi-session terminal emulator, so you can simply and cost-effectively run legacy terminal emulation applications now and Windows GUI or browser-based applications when the time is right.

And the VX6 is supported by LXE's award winning support team, winners of the Mobile Star Award™ for best customer service six years in a row.



Skledar Enterprises Inc.
4243 FM 1173
Krum, TX, 76249

Phone: +972 436 7919
E-mail: sales@sei-integration.com
Web: www.sei-integration.com

VX6

Technical Specifications



Processing & Memory

- Intel® XScale® PXA255 400MHz CPU
- 128MB SDRAM
- 512MB Flash

System Software

- Windows® CE 5.0 Professional
- Windows® CE .NET 4.2

Optional Software

- RFTerm® Windows Terminal Emulations VT220, TN5250, TN3270
- SDK API's
- Personal JAVA 1.2 JVM
- Wavelink Avalanche™ and LXE eXpress Config compatible

Integrated Keyboard

- LXE rugged 60-key keyboard
Features include: 101 key access, backlight, epoxy coating, IP66 seal and terminal emulation specific overlays

Display & Touch Screen

- 10.5" (267mm) TFT active matrix color indoor & outdoor displays with resistive touch screen and tethered stylus
 - ½ SVGA+ = 800 x 320 pixels
 - 550 NIT Brightness (Outdoor Display)
 - 350 NIT Brightness (Indoor Display)
- Front panel brightness adjust
- Optional touch screen heater removes fog or frost from the viewing area
- Screen blanking safety feature

Power Supply & UPS

- 12-80VDC internal fully-isolated power supply with power cable for vehicle attachment
- Externally accessible fuse
- Front panel power switch with power status dual color LED
- Optional UPS lead-acid backup battery pack capable of a minimum 15 minutes operation

Interfaces

- (2) RS-232 Ports (D9) with switchable power for tethered devices like scanners
- (1) Combo USB Host / USB Client / Optional Ethernet Port (10/100Mb)
- (1) 2.5mm Audio / Microphone Jack supports external speakers or headset
- (2) Internal Speakers capable of volumes in excess of 95dB
- Bluetooth®

Expansion

- Expansion device access is via top-mounted user access panel
- (2) Type I/II PCMCIA slots
- (1) SD Memory slot

Radio Card Support - PCMCIA

- 2.4GHz 802.11b/g radios
- 2.4/5GHz 802.11a/b/g radios
- Single or dual diversity external Omni-directional antennas (remote mount antenna kits available)
- WPA or WPA2 security
- Cisco® CCXv4 certified

Enclosure

- Black high strength, high temp industrial plastic with an aluminum mounting plate
- Size: 9.6" x 12.2" x 3.6"
244mm x 309mm x 91mm
- Weight
9.4 lbs (4.26kg)

Environmental

- Operating temperature range:
 - Standard temp unit
-4°F (-20°C) to 122°F (50°C)
 - Freezer unit with heater
-22°F (-30°C) to 122°F (50°C)
 - Storage temperature range
-22°F (-30°C) to 140°F (60°C)
- Humidity
100% RH condensing (heated unit only)
Heated units have conformally coated electronics
- Dust and water protection enclosure rating compliant to IEC 60529 IP66
- Shock and vibration testing exceeds MIL STD 810F

Approvals

- Emissions (EMI)
FCC Part 15 Subpart B, Class A
- Industry Canada ICES-003 Class A
EN 55022, Class A (CISPR22), AS/NZ 3548
- Immunity (EMC)
EN 55024:1998
- Safety
UL 60950, CSA C22.2 No. 60950, EN 60950, IEC 60950
- Radios separately approved to:
FCC Part 15, Subpart C
Industry Canada RSS 210, RSS 102
RSS 139 and/or 210
- R&TTE Directive:
EN 300 328, EN 300 826, EN 60950
- RoHS compliant version available

Vehicle-Mounting

- Mounting Options:
 - RAM® Mount arm system
 - U-bracket mount
 - U-bracket adapter kit to use with existing LXE U-bracket

Accessories

- Remote antenna kits [6' (1.83M)& 8' (2.44M)]
- Tethered scanners (1D and 2D PDF-417)
- Tethered area imagers
- Wireless scanners
- PCMCIA and CF memory cards
- USB/Ethernet conversion cable
- Shielded printer and PC data cables
- Tethered stylus replacement kits
- UPS lead-acid backup battery pack
- UPS battery 6' (1.83M) extension cable
- AC/DC power supply for wall mount applications

