

Bar Code Scanners

Technical Specifications



8800 Wireless Handheld Bluetooth® Scanner 8500 Series Bar Code Scanner

- Extended range scanning from 4 inches to 45 feet.
- Easily reads damaged or poorly printed bar codes (fuzzy logic technology).
- Industrial ergonomics including: IP65, 6.5-ft (2M) drop test, -22° F operating temp.

Scan Rate	Depth of Field	IP Rating	Temp Range	Symbologies Supported
8500 FZY	8500 FZY	8500 FZY	8500 FZY	8500 FZY, 8810 FZ, 8500 ER and 8820 ER UPC.EAN, UPC.EAN with Supplementals, UCC.EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants, and others
8810 FZ	8810 FZ Min. 4.0" Max. 84"	8810 FZ IP65	8810 FZ -22° to 122° F	
8500 ER	8500 ER	8500 ER	8500 ER	
8820 ER	8820 ER Min. 4" Max. 45'	8820 ER IP65	8820 ER -22° to 122° F	
36/ sec.				



8600 Series Bar Code Scanner & Imager

- 2D imager ring with 21" scan distance.
- SR laser ring with 45" scan distance.
- Enhanced white LED flash illumination.
- Either available with long cables to attach to hip-flip or voice case.

Scan Rate	Depth of Field	IP Rating	Temp Range	Symbologies Supported
8600 SRS Imager Series	8600 SRS Imager Min. 3.5" Max. 21"	8600 SRS Imager IP54	8600 SRS Imager -4° to 122° F	8600 SRS Imager & Laser Scanner -1D Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, Interleaved 2 of 5, MSI Plessey, RSS, UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8, EAN-13
8600 SRS Laser Series 36/ sec.	8600 SRS Laser Scanner Min. 1" Max. 45"	8600 SRS Laser Scanner IP54	8600 SRS Laser -4° to 122° F	

*RoHS compliant versions available for all LXE scanners



ORACLE PARTNER



LXE

SEI
Skledar Enterprises Inc.

Skledar Enterprises Inc. Phone: +972 436 7919
4243 FM 1173 E-mail: sales@sei-integration.com
Krum, TX, 76249 Web: www.sei-integration.com